


Brushed Cedar Woodgrain Finish, Contemporary Low-Luster Finish

# HORIZON


vinyl siding

## HORIZON FORTY TWO

.042 Thickness




- Double 4 inch**
- Length 12' - 6"
  - 24 Panels/Ctn.
  - 2 Sq./Ctn.
  - Ctn. Weight: 92.55 lbs.



- Double 4.5 inch Dutchlap**
- Length 12' - 1"
  - 22 Panels/Ctn.
  - 2 Sq./Ctn.
  - Ctn. Weight: 89.05 lbs.

## HORIZON FORTY FOUR

.044 Thickness



- Double 4 inch**
- Length 12' - 6"
  - 24 Panels/Ctn.
  - 2 Sq./Ctn.
  - Ctn. Weight: 95.65 lbs.

.042 Thickness | .044 Thickness

D4

D4.5  
DUTCHLAP

D4

### STANDARD

|                     |   |   |   |
|---------------------|---|---|---|
| 280 White (280)     | ■ | ■ | ■ |
| Cobblestone (33)    | ■ | ■ | ■ |
| Country Beige (509) | ■ | ■ | ■ |

### CLASSIC

|                     |   |   |   |
|---------------------|---|---|---|
| Stone (17)          | ■ | ■ | ■ |
| Clay (43)           | ■ | ■ | ■ |
| Norwegian Wood (34) | ■ | ■ | ■ |
| Storm Gray (174)    | ■ | ■ | ■ |
| Cypress (255)       | ■ | ■ | ■ |

### PREMIUM

|                    |   |   |   |
|--------------------|---|---|---|
| Twilight (767)     | ■ | ■ | ■ |
| Timber Blend (689) | ■ | ■ | ■ |
| Keystone (374)     | ■ | ■ | ■ |

### ELITE

|                    |  |  |   |
|--------------------|--|--|---|
| Bronze (9)         |  |  | ■ |
| Richmond Red (692) |  |  | ■ |
| Hampton Blue (680) |  |  | ■ |

Brushed Cedar Woodgrain Finish, Contemporary Low-Luster Finish



**HORIZON FORTY TWO** Vinyl Siding w/Reinforced Nail Hem meets or exceeds all industry standards per ASTM D3679.

**TEST DATA:**

|                                 |                         |
|---------------------------------|-------------------------|
| Siding Thickness                | 042" ± .001"            |
| Specific Gravity                | 1.45                    |
| Tensile Strength (PSI)          | 7,154                   |
| Tensile Modulus (PSI)           | 416,900                 |
| IZOD Impact Strength @ 32°F     | Passes per ASTM D3679   |
| Heat Deflection Temp. @ 264 PSI | 169°F                   |
| Coefficient of Linear Expansion | 3.30 x 10 <sup>-5</sup> |
| Warpage                         | 0.00"                   |
| Heat Shrinkage                  | 0.3%                    |
| Surface Distortion @ 140°F      | 0                       |

|                           |                       |
|---------------------------|-----------------------|
| Flame Spread Index        | 10                    |
| Fire Rating               | Class A               |
| Smoke Developed           | 395                   |
| Fuel Contribution         | 0                     |
| Average Time Of Burning   | Self extinguished     |
| Average Extent Of Burning | 2.379 mm              |
| Weathering                | Passes per ASTM D3679 |
| Windload Rating*          | 193 MPH               |
| Impact Resistance         | Passes per ASTM D3679 |

\*(Wind Velocity based on IBC)

**HORIZON FORTY FOUR** Vinyl Siding w/Reinforced Nail Hem meets or exceeds all industry standards per ASTM D3679.

**TEST DATA:**

|                                 |                         |
|---------------------------------|-------------------------|
| Siding Thickness                | 044" ± .001"            |
| Specific Gravity                | 1.45                    |
| Tensile Strength (PSI)          | 7,154                   |
| Tensile Modulus (PSI)           | 416,900                 |
| IZOD Impact Strength @ 32°F     | Passes per ASTM D3679   |
| Heat Deflection Temp. @ 264 PSI | 169°F                   |
| Coefficient of Linear Expansion | 3.30 x 10 <sup>-5</sup> |
| Warpage                         | 0.00"                   |
| Heat Shrinkage                  | 0.3%                    |
| Surface Distortion @ 140°F      | 0                       |

|                           |                       |
|---------------------------|-----------------------|
| Flame Spread Index        | 10                    |
| Fire Rating               | Class A               |
| Smoke Developed           | 395                   |
| Fuel Contribution         | 0                     |
| Average Time Of Burning   | Self extinguished     |
| Average Extent Of Burning | 2.379 mm              |
| Weathering                | Passes per ASTM D3679 |
| Windload Rating*          | 193 MPH               |
| Impact Resistance         | Passes per ASTM D3679 |

\*(Wind Velocity based on IBC)